efectorsod

E30130

WELDING ADAPT D50/G1 LEAK PORT



WEEDING ADAP I D30/GI LEAK FOR	Accessores
1: Leakage port	
ACS CRN EC 1935/2004 EHEDG Certified	
Product characteristics	
Welding adapter	
Ø 50 mm	
for units with Aseptoflex Vario adapter	•
Sealing by sealing ring	
Environment	
Pressure rating [bar]	50; for the connection sensor - adapter
MAWP (for applications according to CRN) [bar]	50
Mechanical data	
Process connection	Welding adapter D50
for units with process connection	Aseptoflex Vario
Design	with leakage port
Sealing	with sealing ring
Housing materials	stainless steel 316L / 1.4435
Surface characteristics Ra / Rz of the wetted part(s)	0.4 / 4
Weight [kg]	0.183
Accessories	
Accessories (included)	O-ring 24 x 2 (EPDM), FDA compliant
Accessories (optional)	O-ring 24 x 2 (FPM), FDA compliant, order no. E30123
Remarks	
Pack quantity [piece]	1
ifm electronic gmbh • Friedrichstraße 1 • 45128 Essen	- We reserve the right to make technical alterations without prior notice. $-$ GB $-$ E30130 $-$ 16.04.2013