

Specification: MTDN 2500
Supplier: ismet Transformatoren
Article no.: 720326

- Version:.....Single-phase isolating transformer
- Type:.....MTDN 2500
- Rated output:2500,00 VA
- Rated voltage PRI:.....230-400 V +/- 15 V
- Rated frequency:50 / 60 Hz
- Rated voltage SEC: 15/230 V
- Rated current SEC:21,7/10,8 A (series/parallel conection)
- Test voltage:4,6 kV, VDE 0570 T 2-4, EN 60085
and upon agreement between customer and supplier
- Protection:.....IP 00
- Safety class:I prepared
- Ambient temperature:ta 40/B
- Windings:.....isolated
- Connections:terminals with screwed connections
- Dimension:.....approx. 231 x 245 x 183 mm (BxHxT)
- Weight:approx. 37,00 kg

Mechanical construction

stationary, with holt-foot angles, suitable for mounting up to IP 20,
 screen winding is taken to ground, not on earth terminal
 dimension of fixation 180 x 154 mm, holes of fixation: 8,5 x 20 mm

g

				2018	Date	Name	Specification MTDN 2500 Article no.: 720326	Scale
				Checked	26.06.2018	J.Baur		
				ismet Transformatoren				
				VS-Schwenningen				
Edi tio n	Modificaton	Date	Name					