DEK 5/8 PLUS FSZ 11-20



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com





The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Version	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00 Weidmueller, white	
Order No.	<u>2748030000</u>	
Туре	DEK 5/8 PLUS FSZ 11-20	
GTIN (EAN)	4050118891492	
Qty.	800 pc(s).	

DEK 5/8 PLUS FSZ 11-20



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

5 mm	Height (inches)	0.197 inch
8 mm	Width (inches)	0.315 inch
0.08 g		
-40100 °C		
A4		1
		white
DIACK		No 1 MultiCard = Terminal
Polvamide 66	Number of markers per combination	marker
-40100 °C	Operating temperature range, max.	100 °C
-40 °C		vertical
Numbers		V-2
8 mm	· · ·	
8 mm		
EC000761		EC000761
		27-14-11-37
		27-14-11-37
27-28-11-01	ECLASS 12.0	27-28-11-01
Conform		
Technical change to Dekafix 8 - EN		
<u>Technical change to Dekafix 8 - DE</u> <u>Catalogues in PDF-format</u>		
	0.08 g -40100 °C Weidmueller black Polyamide 66 -40100 °C -40 °C Numbers 8 mm 8 mm 8 mm 8 mm 8 mm Conform Conform Technical change to I Technical change to I	0.08 g -40100 °C Weidmueller Colour black Halogen Number of markers per combination Polyamide 66 -40 °C Operating temperature range, max. -40 °C Orientation of print Numbers UL 94 flammability rating 8 mm EC000761 EC000761 ECLASS 9.0 27:14:11:37 ECLASS 10.0 27:28:11:01 ECLASS 12.0 Conform

DEK 5/8 PLUS FSZ 11-20

Drawings



Weidmüller Interface GmbH & Co. KG Klingenbergstraße 26 D-32758 Detmold

www.weidmueller.com

Germany



Drawing

