

直流轉換器

DC CONVERTER

W 50 X H 84 X D 120mm



規格：

- 精確度：±0.1% FS.(at 23°C)
- 線性度：±0.1% FS.
- 反應時間：0.2sec(0-90%)
- 溫度係數：±0.015% FS/°C
- 環境溫度：-5~+55°C
- 環境濕度：0-90% RH
- 2-Wire輸入附加電源：DC 24~28V未穩壓
- 絕緣阻抗：
≥100MΩ with 500 VDC
- 隔離型（輸入 / 輸出 / 電源間）
- 耐壓強度：AC 1500V，1分鐘
- 隔離型（輸入 / 輸出 / 電源間）
- Case材質：外殼為ABS（黑色），底座為電木
- 零點和範圍調整：±20% FS.
- 消耗電力：4VA

Specifications:

- Accuracy : ±0.1% FS.(at 23°C)
- Linearity : ±0.1% FS.
- Response Time : 0.2sec(0-90%)
- Temp Coefficient : ±0.015% FS/°C
- Operating Temp ; -5~+55°C
- Operating Humidity : 0-90% RH
- 2-Wire Excitation Power : DC 24~28V
- Insulation Resistance :
≥100MΩ with 500 VDC
- Non-Iso. Type(Input, Output/Power)
- Iso. Type(Input/Output/Power)
- Dielectric Strength : AC 1500V, 1 min.
Non-Iso. Type(Input, Output/Power)
- Case Material : Case is ABS, Base is Bakelite
- Zero and Span Adjustment : ±20% FS.
- Power Consumption : 4 VA

型號：Model

TR - [] E [] - [] - []




	直流輸入信號	DC Input	輸入阻抗 I/P Impedance
1	DC 1 - 5 V	1 MΩ	
2	DC 0 - 10 V		
3	DC 0 - 5 V		
4	DC 0 - 1 V		
5	DC 0 - 100 mV		
6	DC 0 - 60 mV		
7	DC 0 - 50 mV		
A	DC 4 - 20mA	50 MΩ	
B	DC 0 - 20mA		
C	DC 0 - 16mA		
D	DC 0 - 10mA		
E	DC 2 - 10mA		
W	2-Wire DC 4-20mA	With Excitation 24V	
F	DC 0 - 1mA	100Ω	
S	Specified		

	直流輸出信號	DC Output	負載阻抗 Load Impedance
1	DC 1 - 5 V	>2.5KΩ	
2	DC 0 - 10 V		
3	DC 0 - 5 V		
4	DC 0 - 1 V		
5	DC 0 - 100 mV		
6	DC 0 - 10 mV		
7	DC ±10 V		
A	DC 4 - 20mA	0-500Ω	
B	DC 0 - 20mA		
C	DC 0 - 16mA		
D	DC 0 - 10mA		
E	DC 2 - 10mA		
F	DC 0 - 1mA		
W	2-Wire DC 4-20mA		
S	Specified		

供應電源 Power Supply

1	AC 110V ± 10% 50/60 Hz
2	AC 220V ± 10% 50/60 Hz
3	DC 24V ± 10%
4	AC 24V ± 10% 50/60 Hz
S	Specified



1	+	OUT	直流輸出 DC Output
2	-		
3	+	IN	直流輸入 DC Input
4	-		
5		PWR	電源 Power
6			
7	U(+)		
8	U(-)		